

PIPEPLUNGER, POLYESTER, IRRADIATED

Product Specification

Product Name:	PipePlunger, Polyester, Irradiated
Manufacturer Part Number(s):	PP6-45LIR and PP6-35LIR
Description:	A Polyester/foam cylinder, for use with the QDPPT-01 or adapters. Manufactured at Micronova's Torrance, CA facility. Designed for pharmaceutical production, medical device, and cleanroom use.
Manufacturing Standards:	ISO 9001: 2008 Facility
Physical Data:	
Materials of Construction:	100% Polyester Polyester Foam
Packaging Materials:	Packaged in LDPE bag, LDPE case liner. ECT rated case of 100% recycled material.
BSE/TSE Statement:	We certify that this product is manufactured without the use of raw materials of animal or human origins.
Dimensions:	PP6-45LIR 4 in x 5 in (10.16 cm x 12.7 cm) PP6-35LIR 3 in x 5 in (7.62 cm x 12.7 cm)
For Use with: (as needed)	QDPPT-01 Adapter, PipePlunger Tool
Autoclavability:	Autoclavable
Chemical Compatibility:	Good compatibility with standard disinfectants and cleaning solutions
Storage Conditions:	Ambient temperature (recommended between 15°C - 30°C). Do not store in direct sunlight. Store the product in a space that is protected from extreme temperature and humidity fluctuations and away from ultraviolet sources.
Packaging Configuration:	Individually double bagged, Irradiation sticker placed on outer bag, 12 per case.
Traceability:	Part number and lot number printed on each bag and each case
Shelf Life:	60 months
Irradiation Standards:	Minimum irradiation dose 25 kGy
Certificates:	Certificate of irradiation shipped with each order